



SECTION: Transportation Services
SUBJECT: Texas Gate Installation

13-12

The installation of a Texas Gate may be permitted on the road allowance subject to the following conditions:

- (a) There must be 200 meters of unobstructed sight distance on each side of the gate.
- (b) There must not be less than 30 meters of level stopping area on each side of the gate.
- (c) The gate must be set on timbers for stability and installed on a level with the existing grade.
- (d) The gate must be constructed of welded metal tubing and suitable pipe - of sufficient strength to carry the maximum allowable loading for the road and must have side plates to keep fill material from falling under the gate.
- (e) The gate must not be less than 7.3 meters (24 feet) in length and 2.5 meters (7.5 feet) wide with removable wings of sufficient width to allow a minimum of 6 meters (20 feet) clearance.
- (f) A suitable approach must be provided to allow a wire gate to be installed adjacent to the Texas gate.
- (g) The responsibility for proper installation and maintenance of the gate will rest solely with the Lessee.
- (h) The gate must be moved and reinstalled at owner's expense if so required by the Special Areas Board (e.g. Road Construction, etc.).
- (i) Failure to comply with any of these conditions may result in the Special Areas Board ordering the removal of the gate or gates.

Approved by Special Areas Board
April 15, 2008 – Motion 7-5-08

Jay J. Slemp, Chairman
Special Areas Board
Revised January, 2010